

Carrying System 3000

Complete ventilation solution in just one hand.

This ergonomically designed Carrying System provides an integrated solution for carrying and transporting an Oxylog 3000 and an oxygen cylinder with a minimum of effort. The frame is small and light with rounded corners to prevent any discomfort in carrying. When a patient is being transported, the complete Carrying System can simply be hung onto a variety of beds and stretchers or onto standard rails.

The bag can be used for storing all kinds of accessories: the patient ventilation tube can easily be stored in the front bag, even when already connected to the Oxylog 3000.

To mount the Carrying System in the All-Round Wall Holder, all you have to do is push one handle - nothing could be easier. The Wall Holder also has an integrated automatic power connection so you no longer need to manually connect a DC/DC converter or AC/DC power supply.



With the Automatic Gas Source Switch, automatic switch-over from central gas supply to cylinder operation and vice versa becomes possible, eliminating the need to reconnect gas

hoses. During switch-over ventilation continues as normal, thus offering smooth therapy.

Specifications

Carrying System 3000

Size (width x height x depth):	515 x 400 x 260 mm / 20.2 x 15.7 x 10.2 inch (standard cylinder bracket)
Weight including Oxylog 3000, 2L GFC cylinder, pressure reducer, oxygen connection tubes.	approx. 14,5 kg / 32 lbs
Cylinder sizes:	
Diameter:	90 mm to 120 mm / 3.5 to 4.7 inch
Length (cylinder bracket: standard):	300 mm to 350 mm / 11.8 to 13.8 inch (excl. valve)
Length (cylinder bracket: long):	300 mm to 500 mm / 11.8 to 19.7 inch (excl. valve)

Order List

Name	Order Number
Carrying System 3000 For carrying, transporting and operating Oxylog 3000 when no external power supply or central gas supply is available. Including carrying frame, accessories bag, adapter for quick power connection and cylinder bracket available in two lengths.	2M86 975
To choose:	
Cylinder bracket standard (1 - 2.5L) For cylinders up to 120 mm / 4.7 inch diameter and 350 mm / 13.8 inch length.	5704449
Cylinder bracket long (1 - 3L) For cylinders up to 120 mm / 4.7 inch diameter and 500 mm / 19.7 inch length.	5704589
Oxygen supply:	
Gas Supply System To connect the Oxylog with an oxygen cylinder and/or a central gas supply. The central gas supply is automatically selected by the optional Automatic Gas Source Switch when the oxygen cylinder and central gas supply are simultaneously connected. Including oxygen connection tubes and optional pressure reducer.	5704500
Optional accessories:	
All-Round Wall Holder	5704216
All-Round Wall Holder USA	5704641
Quick Power Connector	5704217

Europe, Middle East, Africa, Latin America,
Asia, Pacific:

Dräger Medical AG & Co. KG
Moislinger Allee 53-55
23542 Lübeck
GERMANY
Tel: +49-1805-3 72 34 37
+49-451-882-822
Fax: +49-451-882-37 79
E-mail:
Business.Support@draeger.com

USA:

Draeger Medical, Inc.
3135 Quarry Road
Telford, PA 18969
USA
Tel: +1-215-721-5400
Toll-free: +1-800-437-2437
Fax: +1-215-723-5935
E-mail: info@draegermed.com

Canada:

Draeger Medical Canada Inc.
120 East Beaver Creek Road
Suite 104
Richmond Hill Ontario L4B 4V1
CANADA
Tel: +1-905-763-3702
Toll-free: +1-866-343-2273
Fax: +1-905-763-1890
E-mail:
Canada.Support@draeger.com

www.draeger.com

Manufacturer: Dräger Medical b.v., NL-5683 CR Best

The quality management system at Dräger Medical b.v. is certified according to ISO 13485, ISO 9001 and Annex II of Directive 93/42/EEC (Medical devices).