

Infinity® C700 for IT Workstation

Today, a patient-vicinity IT workstation is a necessity for bringing integrated clinical information to the point of care. The Infinity® C700 for IT is a state-of-the-art medical device that displays patient vital sign data, clinical software applications, and networked information at the point of care.



The Infinity C700 for IT combines a CPU with a 20" touchscreen color display designed for use at the patient vicinity. The widescreen format offers a large viewing angle for increased visibility, while the Surface Acoustic Wave (SAW) touchscreen technology provides high image clarity with a sturdy all-glass panel that is ideal for hygienic environments.

The 20" widescreen format makes it easy to display information in a split screen presentation, while the fan-less design reduces dust and noise level.

The Infinity C700 for IT supports clinical decision-making as either a patient-vicinity PC or as the widescreen component of the Infinity Omega solution.



Infinity C700 for IT workstation
Combines CPU with 20" touchscreen display, space-saving profile, and quiet fan-less design.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS

H x W x D	486 mm x 337 mm x 127.5 mm (19.13 x 13.27 x 5.02)
Weight	11.2 kg (24.7 lbs)
Cooling	Convection
Touchscreen	Surface Acoustic Wave (SAW)
CPU	INTEL Pentium M 1.4 GHz with 2 MB L2 Cache
Memory	1 GB (DDR2 533 SODIMM)
Power MTBF	Minimum 100,000 hours
Operating system	Microsoft Windows® XP Pro
Computer memory and realtime clock backup battery	3 V lithium coin cell (part number MS22812)

CONTINUING TECHNICAL SPECIFICATIONS

Connectors	3 external RS232 (9-pin) connectors (not used) 4 USB ports (on the back panel) 2 USB ports (on the side panel) 1 DVI for independently configurable display with touch screen control (not enabled with Infinity Explorer) 2 DVI for independently configurable display output supporting up to 1920 x 1200 resolution (not enabled with Infinity Explorer) 2 RJ45 Ethernet connectors to connect to safety extra-low voltage (SELV) networks
Input voltage	18V to 30V DC, 5.5 A/3.3 A max
Rotary knob (optional)	Navigation tool

DISPLAY SPECIFICATIONS

Resolution (max)	1680 x 1050
Colors	262,000
Contrast ratio	500:1
LCD MTBF	50,000 hours
Viewing angle	170 degrees
Display type	51 cm (20.1 inch) TFT wide screen LCD
Dot size (mm)	0.258 mm

ENVIRONMENTAL REQUIREMENTS

Temperature

Operating	0° C to 40° C (32° F to 104° F)
Storage	-20° C to 60° C (-4° F to 140° F)

Relative humidity

Operating	10% to 95% (non-condensing)
Storage	5% to 95% (non-condensing)

Atmospheric pressure

Operating	70 to 106 kPa
Storage	50 to 106 kPa

Altitude	0 to 3048 m (0 to 10,000 feet)
----------	--------------------------------

Standards

FCC, Class B
IEC 60601-1: (EN60601-1)
CAN/CSA 22.2 No 601.1 M90 (with release to Canada)
UL 60601-1 (with release to U.S.)
IEC 60601-1-1: 2000 Medical Electrical System
IEC 60601-1-2:2001, EMC overall standard

Liquid ingress protection	IPX1 (drip-proof) per IEC 60529
Packaged Shock and Vibration	Per ISTA procedure 1
Operational shock	30 G, half-sine, 11 ms, 600 total shocks, per IEC 60068-2-27
Operational vibration	IEC 60068-2-6 (0.047 double amplitude displacement (5-32 Hz) 2G (32-500 Hz))
Random vibration	1.04 g rms, broadband, 10 to 500 Hz, 6 hours, per IEC 60068-2-64

Power Supply (120 watts)

CAUTION: Always use a power cord with a hospital-grade plug.

Physical Attributes

Connections	System cable
Cooling	Convection – non vented case
Size (W x D x H)	74 mm x 51 mm x 229 mm (10.93 x 2.0 x 2.9)
Weight	684 grams, 24 ounces (excluding cord)
Power requirements	Voltage – 100 to 240 VAC (50 to 60 Hz, 2.0 A) MBTF - Minimum 100,000 hours
DC output	+24V/5 A
Protection class	Class I
Mode of operation	Continuous
Liquid ingress protection	IPX 0 per IEC 60529

ENVIRONMENTAL REQUIREMENTS

Temperature range

Operating	0° C to 40° C (32° F to 104° F)
Storage	-30° C to 85° C (-22° F to 185° F)

Relative humidity

Operating	10% to 95% (non-condensing)
Storage	5% to 95% (non-condensing)

Atmospheric pressure

Operating	70 to 106 kPa
Storage	50 to 106 kPa

Altitude	0 to 3048 m (0 to 10,000 feet)
----------	--------------------------------

Standards

Complies with IEC 60601-1 and IEC 60601-1-2 with applicable regional/national deviations

ORDERING INFORMATION

Infinity C700for IT Workstation	MS22249
120 watt power supply for use with the Infinity C700 for IT	MS20749
Rotary knob (optional)	MS22771

For a list of available languages, contact your Dräger sales representative.

HEADQUARTERS

Dräger Medical AG & Co. KG
 Moislinger Allee 53–55
 23558 Lübeck, Germany

www.draeger.com

**EUROPE, MIDDLE EAST, AFRICA,
LATIN AMERICA, ASIA, PACIFIC**

Dräger Medical AG & Co. KG
 Moislinger Allee 53–55
 23558 Lübeck, Germany
 Tel +49 451 882-0
 Fax +49 451 882-2080
info@draeger.com

CANADA

Draeger Medical Canada Inc.
 120 East Beaver Creek Road Suite 104
 Richmond Hill Ontario L4B 4V1, Canada
 Tel +1 905 763-3702
 Toll-free +1 866 343 22 73
 Fax +1 905 763-1890
Canada.Support@draeger.com

USA

Draeger Medical, Inc.
 3135 Quarry Road
 Telford, PA 18969, USA
 Tel +1 215 721 5400
 Toll-free +1 800 437 24 37
 Fax +1 215 723 59 35
info.usa@draeger.com

Manufacturer:

Dräger Medical AG & Co. KG
 23542 Lübeck, Germany
 The quality management system at
 Dräger Medical AG & Co. KG is
 certified according to ISO 13485,
 ISO 9001 and Annex II.3 of Directive
 93/42/EEC (Medical devices).